



Kidde Residential and Commercial
• Pro Line





Kidde is a leading global supplier of fire and safety products, systems and services under a range of well-known and trusted brand names to industrial, commercial, aerospace, combustion control and retail customers. The Kidde Group comprises three divisions: Aerospace & Specialist Equipment, Residential & Commercial Fire Protection and Industrial Fire Protection and has operating companies in 29 countries together with worldwide distribution for its products and systems.

Kidde Residential & Commercial is the world's leading manufacturer of home safety products, including fire extinguishers, carbon monoxide alarms, smoke alarms and fire escape ladders.

**Kidde Residential and
Commercial Division
1394 South Third Street
Mebane, NC 27302
Tel. 919.563.2711
www.kiddeUS.com**



Pro 2.5 MP Fire Extinguisher

Part number 466227

Multipurpose use

Rechargeable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Available with metal retention bracket.
Order pt # 46622701


At a Glance

- Model PRO 2.5MP
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.6 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection
- Optional metal strap bracket Pt # 466401

For use on the following types of fire:



UPC: 0-47871-66227-2

Product Specification

Net agent weight (Average)	2.6 lb
Unit weight (Average)	3.9 lb
Diameter	3.25 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 4 MP Fire Extinguisher

Part number 466288

Multipurpose use

Rechargeable

UL Rated 2-A,10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 4 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Robust handle, lever and valve assembly
- 4 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection

At a Glance

- Model Pro 4 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 2-A, 10-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66288-3

Product Specification

Net agent weight (Average)	4.0 lb
Unit weight (Average)	7.0 lb
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



Pro 5 MP Fire Extinguisher

Part number 466112

Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 5 MP unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 466400

At a Glance

- Model Pro 5 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:




UPC: 0-47871-66112-0

Product Specification

Net agent weight (Average)	5.0 lb
Unit weight (Average)	7.9 lb
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



Kidde Residential and Commercial Division
1394 South Third Street, Mebane, NC 27302 • Tel. 919.563.2711 • www.kiddeus.com



Pro 10 MP Fire Extinguisher

Part number 466204

Multipurpose use

Rechargeable

UL Rated 4-A, 60-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 10 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 10 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 366242

At a Glance

- Model Pro 10 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 4-A, 60-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66204-3

Product Specification

Net agent weight (Average)	10 lb
Unit weight (Average)	16 lb
Diameter	5.21 inches
Height	19.52 inches
Discharge time	19-21 seconds
Discharge range	20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Aluminum
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Kidde Residential and Commercial Division
1394 South Third Street, Mebane, NC 27302 • Tel. 919.563.2711 • www.kiddeus.com



Pro 20 MP Fire Extinguisher

Part number 466206

Multipurpose use

Rechargeable

UL Rated 10-A, 80-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 20 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 20 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 292474

At a Glance

- Model Pro 20 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 10-A, 80-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66206-7

Product Specification

Net agent weight (Average)	20 lb
Unit weight (Average)	30 lb
Diameter	7.0 inches
Height	21.6 inches
Discharge time	19-22 seconds
Discharge range	20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Aluminum
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 2.75 R Fire Extinguisher

Part number 466228

Regular use

Rechargeable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).


The Pro 2.75 R is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Available with metal retention bracket.
Order pt # 46622801

At a Glance


- Model Pro 2.75 R
- Regular Dry Chemical
- Rechargeable
- UL listed
- UL rated 10-B:C
- U.S.C.G., DOT approved
- Supplied with plastic retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.9 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hook
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection
- Optional metal strap bracket Pt # 466401



UPC: 0-47871-66228-9

Product Specification

Net agent weight (Average)	2.9 lb
Unit weight (Average)	4.38 lb
Diameter	3.25 inches
Height	14.4 inches
Discharge time	8-12 seconds
Discharge range	8-12 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 10 R Fire Extinguisher

Part number 466205

Regular use

Rechargeable

UL Rated 60-B:C



Description


Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 10 R unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.

At a Glance

- Model Pro 10 MP
- Regular Dry Chemical
- UL listed
- UL rated 60-B:C
- Supplied with wall hanger
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 10 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 466401



UPC: 0-47871-66205-0

Product Specification

Net agent weight (Average)	10 lb
Unit weight (Average)	16 lb
Diameter	5.21 inches
Height	19.52 inches
Discharge time	19-25 seconds
Discharge range	20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Aluminum
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 20 R Fire Extinguisher

Part number 466207

Regular use

Rechargeable

UL Rated 80-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 20 R unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 21.6 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 292474

At a Glance

- Model Pro 20 R
- Regular Dry Chemical
- UL listed
- UL rated 80-B:C
- Supplied with wall hanger
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66207-4

Product Specification

Net agent weight (Average)	20 lb
Unit weight (Average)	29.31 lb
Diameter	7.2 inches
Height	21.0 inches
Discharge time	20-25 seconds
Discharge range	16-20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Aluminum
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 5 CD Fire Extinguisher

Part number 466180

Electrical risks

Rechargeable

UL Rated 5-B:C



Description


Suitable for use on Class B (liquids) and Class C fires (energized electrical equipment).

The Pro 5 carbon dioxide unit is environmentally safe and ideal for protecting delicate electronic equipment as the clean agent leaves no residue. The cylinder is manufactured from aluminum and the valve assembly is metal.

Features

- Agent will not contaminate food, valuable materials or electronics
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb of fire extinguishing agent (Average)
- 5 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



At a Glance

- Model Pro 5 CD
- Carbon dioxide
- UL listed
- UL rated 5-B:C
- Supplied with wall hanger
- 5 year limited warranty
- Suitable for use on energized electrical equipment

UPC: 0-47871-66180-0

Product Specification

Net agent weight (Average)	5 lb
Unit weight (Average)	15.0 lb
Diameter	5.25 inches
Height	17.0 inches
Discharge time	7-9 seconds
Discharge range	3-8 feet
Operating pressure	850 psi
Cylinder	Aluminum
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 10 CD Fire Extinguisher

Part number 466181

Electrical risks

Rechargeable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids) and Class C fires (energized electrical equipment).

The Pro 10 carbon dioxide unit is environmentally safe and ideal for protecting delicate electronic equipment as the clean agent leaves no residue. The cylinder is manufactured from aluminum and the valve assembly is metal.


Features

- Agent will not contaminate food, valuable materials or electronics
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 10 lb of fire extinguishing agent (Average)
- 5 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

At a Glance

- Model Pro 10 CD
- Carbon dioxide
- UL listed
- UL rated 10-B:C
- Supplied with wall hanger
- 5 year limited warranty
- Suitable for use on energized electrical equipment

For use on the following types of fire:



UPC: 0-47871-66181-7

Product Specification

Net agent weight (Average)	10 lb
Unit weight (Average)	30.0 lb
Diameter	6.87 inches
Height	19.37 inches
Discharge time	8-10 seconds
Discharge range	3-8 feet
Operating pressure	850 psi
Cylinder	Aluminum
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 15 CD Fire Extinguisher

Part number 466182

Electrical risks

Rechargeable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids) and Class C (energized electrical equipment).

The Pro 15 carbon dioxide unit is environmentally safe and ideal for protecting delicate electronic equipment as the clean agent leaves no residue. The cylinder is manufactured from aluminum and the valve assembly is metal.


Features

- Agent will not contaminate food, valuable materials or electronics
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 15 lb of fire extinguishing agent (Average)
- 5 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

At a Glance

- Model Pro 15 CD
- Carbon dioxide
- UL listed
- UL rated 10-B:C
- Supplied with wall hanger
- 5 year limited warranty
- Suitable for use on energized electrical equipment

For use on the following types of fire:



Product Specification

Net agent weight (Average)	15 lb
Unit weight (Average)	40.0 lb
Diameter	6.87 inches
Height	26.0 inches
Discharge time	12-14 seconds
Discharge range	3-8 feet
Operating pressure	850 psi
Cylinder	Aluminum
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Pro 20 CD Fire Extinguisher

Part number 466183

Electrical risks

Rechargeable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids) and Class C fires (energized electrical equipment).

The Pro 20 carbon dioxide unit is environmentally safe and ideal for protecting delicate electronic equipment as the clean agent leaves no residue. The cylinder is manufactured from aluminum and the valve assembly is metal.


Features

- Agent will not contaminate food, valuable materials or electronics
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 20 lb of fire extinguishing agent (Average)
- 5 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

At a Glance

- Model Pro 20 CD
- Carbon dioxide
- UL listed
- UL rated 10-B:C
- Supplied with wall hanger
- 5 year limited warranty
- Suitable for use on energized electrical equipment

For use on the following types of fire:



UPC: 0-47871-66183-1

Product Specification

Net agent weight (Average)	20 lb
Unit weight (Average)	51.0 lb
Diameter	8.0 inches
Height	26.0 inches
Discharge time	15-17 seconds
Discharge range	3-8 feet
Operating pressure	850 psi
Cylinder	Aluminum
Valve, handle, lever	Brass & stainless steel
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK